Amendments to the claims:

Claims 1-14: (canceled)

- 15. (currently amended) An electric power tool, having an electric motor (8) acting to drive a tool (6) and having a sensor unit (9), which detects the contact pressure of the tool (6) against a workpiece (7) and cooperates with a signal transducer (10), wherein the sensor unit (9) has a current-measuring device (23), which detects the current of the electric motor (8), and wherein the sensor unit (9) has a strain gauge and/or a piezoelectric sensor.
- 16. (currently amended) An electric power tool, having an electric motor (8) acting to drive a tool (6), having a control and/or regulating unit (20) serving to guide the operation of the electric motor (8) and having a sensor unit (9), which detects the contact pressure of the tool (6) against a workpiece (7) and cooperates with the control and/or regulating unit (20), wherein the sensor unit (9) has a strain gauge and/or a piezoelectric sensor has a current measuring device (23), which detects the current of the electric motor (8).
- 17. (previously presented) The electric power tool in accordance with claim 16, wherein the sensor unit (9) cooperates with a signal transducer (10).
 - 18. (canceled)

- 19. (currently amended) The electric power tool in accordance with claim 15 or 16, wherein the current-measuring device (23) has a shunt (31), through which the motor current flows, and an electronic evaluation unit (36).
- 20. (previously presented) The electric power tool in accordance with claim 15, wherein the signal transducer (10) is an optical and/or an acoustical signal transducer (12, 13) and/or a signal transducer (14) that calls on the sense of touch.
- 21. (previously presented) The electric power tool in accordance with claim 20, wherein the optical signal transducer (12) is at least one LED (15, 16) and/or an LED array (17) and/or a display (19) and/or a bar display (18).
- 22. (previously presented) The electric power tool in accordance with claim 20, wherein the acoustical signal transducer (13) is a speaker and/or a bell.
- 23. (previously presented) The electric power tool in accordance with claim 22, wherein a device that has a sound output in the form of a speech output is associated with the speaker.
 - 24. (previously presented) The electric power tool in accordance with

claim 16, wherein the control and/or regulating unit (20) controls and/or regulates the torque of the tool (6), or of a tool receptacle (6'), as a function of the contact pressure of the tool (6) against the workpiece (7).

- 25. (previously presented) The electric power tool in accordance with claim 16, wherein the control and/or regulating unit (20) controls and/or regulates the rotary speed of the tool (6), or of a tool receptacle (6'), as a function of the contact pressure of the tool (6) against the workpiece (7).
- 26. (previously presented) The electric power tool in accordance with claim 16, wherein the control and/or regulating unit (20) controls and/or regulates the torque of the tool (6), or of a tool receptacle (6'), as a function of the contact pressure of the tool (6) against the workpiece (7) at a predetermined rotary speed.
- 27. (currently amended) A method for guiding the operation of an electric power tool that has an electric motor (8) acting to drive a tool (6), comprising the following steps:

detecting the current of the electric motor (8) with a current-measuring device (23);

determining the contact pressure of the tool (6) against a workpiece (7) from the current of the electric motor (8);

automatically adjusting a torque and/or a rotary speed of the electric

motor.

outputting the contact pressure to enable the changing of the contact pressure of the tool (6) by the user.

28. (previously presented) A method for guiding the operation of an electric power tool that has an electric motor (8) acting to drive a tool (6), comprising the following steps:

detecting the current of the electric motor (8) with a current-measuring device (23);

determining the contact pressure of the tool (6) against a workpiece (7) from the current of the electric motor (8);

automatically adjusting the torque of the electric motor (8), of a tool (6), and/or of a tool receptacle (6'), as a function of the contact pressure, taking a predetermined rotary speed into account.

- 29. (new) The electric power tool in accordance with claim 16, wherein the sensor unit (9) has a current measuring device (23), which detects the current of the electric motor (8).
- 30. (new) The electric power tool in accordance with claim 15, wherein the signal transducer (10) is an acoustical signal transducer (13).
 - 31. (new) The electric power tool in accordance with claim 15, wherein

the signal transducer (10) is a signal transducer (14) that calls on the sense of touch.

32. (new) An electric power tool, having an electric motor (8) acting to drive a tool (6), having a control and/or regulating unit (20) serving to guide the operation of the electric motor (8) and having a sensor unit (9), which detects a contact pressure of the tool (6) against a workpiece (7) and cooperates with the control and/or regulating unit (20), wherein the control and/or regulating unit regulates a torque and/or a rotary speed of the electric motor (8) as a function of the contact pressure of the tool (6) against the workpiece (7).